

HECKMAN

TECHNOLOGY serves MAN



WLFP51100A

European product
EAN Code 590



5 905562 027111 >



Safety

Advanced BMS - LiFePO4 technology



Single module capacity

5,12kWh, battery cell Grade "A"



Ease of installation

Modular rack 19" 3U construction



Scalability

Possibility of connecting parallel modules up to 80kWh



Compatibility

Cooperation with most of low-voltage inverters



Efficiency

High charging and discharging current



HECKMAN

TECHNOLOGY serves MAN

Technical data

Producer brand	Heckman	Heckman	Heckman
Product model	WLFP51100A/100	WLFP51100A/50	WLFP51100A/20
Nominal voltage	51 V	51 V	51 V
Cells capacity	100 Ah	100 Ah	100 Ah
Number of cells	16 S	16 S	16 S
Technology	LiFePO4	LiFePO4	LiFePO4
Battery cell grade	Grade A	Grade A	Grade A
Nominal capacity	5120 Wh/5,12 kWh	5120 Wh/5,12 kWh	5120 Wh/5,12 kWh
Usable capacity	4860 Wh/4,86 kWh	4860 Wh/4,86 kWh	4860 Wh/4,86 kWh
Nominal charge/discharge power	4,86 kW	2,43 kW	0,97 kW
Efficiency	95 %	95 %	95 %
Max. charge/discharge power	<= 100A (1C)	<= 50A(0,5C)	<= 20A(0,2C)
Recommended charging current	30A(0,3C)	30A(0,3C)	20A(0,2C)
Discharge overcurrent protection	105A alarm, 110A switch-off	55A alarm, 60A switch-off	25A alarm, 30A switch-off
Charge overcurrent protection	100A alarm, 110A switch-off	50A alarm, 60A switch-off	20A alarm, 30A switch-off
Possibility to combine modules	parallel up to 16pcs. (81,92 kWh)	parallel up to 16pcs. (81,92 kWh)	parallel up to 16pcs. (81,92 kWh)
Communication interface	CAN/RS-485	CAN/RS-485	CAN/RS-485
Charge level indicator - SoC	LED	LED	LED
TurnOff Switch	YES	YES	YES
EPO - fire protection	YES	YES	YES
Work mode indicator	LED	LED	LED
Operating mode selection	DIP switch	DIP switch	DIP switch
Dimensions W x L x H (mm)	460 x 170 x 600 mm	460 x 170 x 600 mm	460 x 170 x 600 mm
Weight	54 kg	54 kg	54 kg
Noise level	0 dB	0 dB	0 dB
Working temperature	-15°C - 60°C	-15°C - 60°C	-15°C - 60°C
Charging temperature	0°C - 55°C	0°C - 55°C	0°C - 55°C
Humidity	≤90 % (40°C ± 2°C)	≤90 % (40°C ± 2°C)	≤90 % (40°C ± 2°C)
IP protection level	IP21	IP21	IP21
Warranty	10 years	10 years	10 years

HECKMAN Sp. z o.o.
Kolumba Street 43/47
02-288 Warsaw, POLAND

VATEU: PL9522156846

+48 22 100 59 60
contact@heckman.eu